Working effectively with ultra-high pressure (UHP) water technology

MICROpremium flex CLEANER

The MICROpremium flex modular system can be used in a variety of ways thanks to different components. With the ultra-high pressure (UHP) water device CLEANERbasic you can remove deposits, concrete and other materials with up to 2,500 bar water pressure. It can be used in all pipe materials with nominal diameters from DN 100 to DN 250. Different nozzles are available depending on the nature and planned work.

IMS Robotics GmbH
Am Bauhof 6
D-01458 Ottendorf-Okrilla
Fax: +49 35205 53749

+49 35205 7555-0
info@ims-robotics.de
ims-robotics.de

Technical Data

Measurements	Outer diameter: 75 mm / 2.95 inches Length CLEANER head: approximately 920 mm / 36.22 inches
Nominal Diameter	Usable in pipes from DN 100 to DN 250 (inner diameter)
Weight	Weight UHP module: approximately 8 kg / 17.64 pounds
Components	Nozzle carrier, plug-in nozzle and extension parts
Camera	Colour camera with adjustable LED illumination and wiper
Cable Length / Cable Drum	Cable length up to 70 m
Features / Special Features	Maximum water pressure from 0 to 2500 bar Can be bent in KG pipes from DN 125 (depending on pipe condition) Pneumatic pressure rail for better stability and traction CLEANER head: Rotary-swivel actuators, rotate endlessly, swivel 45°, speed adjustable Rotary-swivel actuator watertight with 0.8 bar nitrogen filling Nozzle carrier for working pressures up to 2500 bar Original equipment insert nozzle Ø 0.95 mm for 19 l/min at 2500 bar
Additional Purchase Options	Bracing unit for CLEANER

IMS Robotics GmbH
Am Bauhof 6
D-01458 Ottendorf-Okrilla
Fax: +49 35205 53749

+49 35205 7555-0
info@ims-robotics.de
ims-robotics.de