

The modular system for house connection


MICROpremium flex

In its basic configuration, the MICROpremium flex modular system consists of a cable drum and a control unit. These can be combined with the MICROpremium cutting robot. Applicable from DN 80 to 250, the house connection cutter has a good bendability of 90° from DN 100. On the other hand, the CLEANERbasic can be connected. The ultra-high pressure (UHP) water head can also be used in DN 100 to DN 250 and uses a maximum water pressure of up to 2,500 bar.



IMS Robotics GmbH
Am Bauhof 6
D-01458 Ottendorf-Okrilla
Fax: +49 35205 53749

+49 35205 7555-0
info@ims-robotics.de
ims-robotics.de



Technical Data

Measurements	Cable drum size: L 790 x W 630 x H 1050 mm (or L 31.1 x W 24.8 x H 41.34 inches)
Weight	Weight cable drum: approximately 81 kg with 50 m supply hose length / approximately 89 kg with 70 m supply hose length.
Components	Cable drum and control unit Optional with cutter module MICROpremium flex, MICROMotion or ultra-high pressure (UHP) head CLEANERbasic
Cable Length / Cable Drum	50 m / 164.04 ft or 70 m / 229.66 ft supply hose on cable drum Cable drum with pneumatic and electrical rotary transmission and manual brake
Control	Control unit with holder for HDMI display and 2 multifunctional joysticks PLC control with touch screen
Features / Special Features	Removable control unit in protective case with video PC and HDMI display with touch screen
Additional Purchase Options	5 m / 16.4 ft extension cable for control unit Vehicle installation set

IMS Robotics GmbH
Am Bauhof 6
D-01458 Ottendorf-Okrilla
Fax: +49 35205 53749

+49 35205 7555-0
info@ims-robotics.de
ims-robotics.de